





Fuel Filters Information Sheet

| Filter Type | Image | Description | Filter Spec | Maximum Flow Rate | Flow Direction | Inlet/Outlet | Colors | Elements |
|-------------|---|---|-------------|---|------------------|--------------------------------|-----------------------|--|
| 4501 series |  | High flow canister style Fuel Filter. CNC machined and hand polished. Integral mounting bracket makes installation a breeze. May also be used for fuel injection. | 10 Micron | 225 Gallons per Hour (GPH) | In & Out | -06 AN Female -08 AN Female | Black Clear | <ul style="list-style-type: none"> ▪ 10 Micron paper fuel filter element w/ O-rings ▪ 40 Micron Stainless Steel fuel filter element w/ O-rings ▪ 100 Micron Stainless Steel fuel filter element w/ O-rings ▪ Replacement O-rings |
| 4651 series |  | 6" In line race fuel filter* | 40 Micron | 225 Gallons per Hour (GPH) | Follow arrow out | -6, -8 and -10 | Black Clear Red | <ul style="list-style-type: none"> ▪ Holder- color options: black, clear, red ▪ 10 Micron Stainless Steel fuel filter element w/ O-rings ▪ 100 Micron Stainless Steel fuel filter element w/ O-rings ▪ Replacement O-rings |
| 4151 series |  | AN Style Fuel Filters** | 100 Micron | 130 Gallons per Hour (GPH) at 75 PSI | Either direction | -6, and -8 | | <ul style="list-style-type: none"> ▪ Replacement O-rings |
| 4152 series |  | One Way Check Valve | n/a | Includes Teflon® valve, 5 PSI opening for the valve | Follow arrow out | -04, -06, -08, -10 and -12 | | <ul style="list-style-type: none"> ▪ Replacement O-rings |

** All filters include a serviceable stainless element, pressure rating of 500psi and a nominal micron rating of 100. 130 gallon per hour at 75 PSI for both -06 and -08.